

INTRODUCING SUPERA



**BETTER PERFORMANCE,
SAME COMPETITIVE PRICE**

Passive House performance at
conventional window prices



WHY SUPERA?

- + Increased thermal performance
- + Arcade-level prices
- + AW & CW class ratings available
- + Excellent for Passive House
- + Highest industry standards for water and air infiltration
- + DP 70 structural ratings
- + Industry-leading warranty

LAUNCHING
MAY 2019

 INTUS WINDOWS


TEST REPORTS

FIXED WINDOWS



NFRC Values

U-value (BTU/hr.ft ² .°F)	0.14–0.28
SHGC (Solar Heat Gain Coefficient)	0.17–0.51
VT (Visual Transmittance)	0.34–0.66





CW OPERABLE WINDOWS



NFRC Values

U-value (BTU/hr.ft ² .°F)	0.17–0.28
SHGC (Solar Heat Gain Coefficient)	0.12–0.43
VT (Visual Transmittance)	0.22–0.56




AW OPERABLE WINDOWS



NFRC Values

U-value (BTU/hr.ft ² .°F)	0.18–0.29
SHGC (Solar Heat Gain Coefficient)	0.11–0.42
VT (Visual Transmittance)	0.20–0.54



AWNING OPERABLE WINDOWS



NFRC Values

U-value (BTU/hr.ft ² .°F)	0.21–0.28
SHGC (Solar Heat Gain Coefficient)	0.10–0.28
VT (Visual Transmittance)	0.18–0.36

